blueparrott GN

BlueParrott M300-XT

ENGINEERED TO KEEP YOU CONNECTED ON THE GO.

Our smallest and lightest Bluetooth® headset with 80% noise cancellation.

- > 80% noise cancellation with 2-mic tech
- > Just 0.7 oz / 20 g for all day comfort
- IP54-rated protection against dust and moisture
- > Up to 14 hours of talk time
- > Up to 300 ft / 100 m wireless range
- > Customizable BlueParrott Button™



TECHNICAL SPECIFICATIONS			
Audio	Noise reduction on calls	Yes	
	Speaker size	10.3mm 0.41in	
	Speaker max input power	5 mW	
	Speaker frequency range	20Hz	
	Speaker impedance	32 Ω	
	Audio codecs supported	SBC	
	Microphone type	2 x MEMS	
	Microphone sensitivity	-42±1dB (0dB=1V/Pa, at 1KHz)	
	Certifications and compliance	FCC, ISED, CE, RoHS, REACH, Proposition 65	
Fit & Comfort	Form factor	BT Mono	
	EarGels	Large, medium, small	
Connectivity	Connectivity	Bluetooth	
	BlueParrott button	Yes	
	Bluetooth® profiles	A2DP v1.3, HFP v1.7, HSP v1.2	
	Bluetooth® version	5.1	
	Operating range (Bluetooth)	Up to 100m 300ft	
	Paired devices	Up to 8 Bluetooth devices	
	Simultaneous Bluetooth connections	2	
	NFC (Near Field Communication)	Yes	
Battery	Talk time	Up to 14 hours	
	Corded charging	USB-C™	
	Charging time	Up to 150 minutes	
	Standby time	Up to 420 hours	
	Battery type	Rechargeable lithium-ion battery	
Software & Apps	Compatible software and/or apps	BlueParrott App, BlueParrott Updater	
	Over-the-air firmware updates	Yes	

TECHNICAL SPECIFICATIONS				
General info	Box contents	Headset, 3 sets of EarGels™, user documents, USB cable		
	Packaging dimensions (WxHxD)	41.5mm x 175mm x 131mm 1.63in x 6.89in x 5.16in		
	Main unit dimensions (WxHxD)	110.7mm x 61mm x 25.4mm 4.36in x 2.4in x 1in		
	Main unit weight	20g 0.7oz		
	USB cable length	1.2m 3.9ft		
	IP rating (main unit)	IP54		
	Warranty	1 year		
Extended info	Operating temperature	-10°C to 60°C 14°F to 140°F		
	Storage temperature	-10°C to 45°C 14°F to 113°F		

PRODUCT TYPE	SKU	DESCRIPTION
Products	204347	BlueParrott M300-XT
Accessories	204354	BlueParrott M300-XT Refresher Kit