

MOUNTING LOCATION:

Upper left side of radio JL

TOOLS REQUIRED:

Dash Tool

Torx 15 Tool

Phillips Screwdriver

HARDWARE INCLUDED:

(1) S75105-621 (InDash Mount)

(1) T8-750NPB (Needle nose screw)

CELL PHONE & MEDIA MOUNT

INSTALLATION INSTRUCTIONS

PART#: 75105-621

MFG: RAM

MODELS & YEARS:

1500-5500

2019-2021

** ADVISEMENT **

Read instructions completely prior to starting installation. All InDash Mounts are designed so that after installation, phone is facing normal driver position for left-hand drive vehicles. This mount is not designed to be used in foreign countries with right-hand drive vehicles. Use extreme care when working around the plastic components on the dash. Excess force, can cause breakage of the plastic components.

STEP #1: Remove the top rubber tray to expose (2) Torx 15 screws. Remove screws, and set aside alongside the rubber tray.

STEP #2: Sit in the center seat of the cabin, so that you are directly behind the radio unit. With a firm grip, pull towards your body until all (9) clips are released.

STEP #3: Select one of the top (4) mounting locations, and remove the screw with a Phillips head screwdriver. Place said screw through the slot on the InDash unit, and secure it to the dashboard. Ensure proper faceplate orientation, and if necessary install the provided screw for increased stability.

STEP #4: Replace radio unit and ensure all (9) clips are secured.

STEP #5: Replace (2) Torx 15 screws on the top of the unit, and cover those with the rubber tray.

INSTALLATION IS NOW COMPLETE. ENJOY YOUR NEW INDASH by PANAVISE MOUNT



Torx screw locations



Hand placement on radio unit



InDash Mount Installed



Screw installation (left-most spot)



Mounting locations

Support screw location

06-14-21

