



Product Features

- Quick and easy on-site installation
- Made with 1¼" (3.2 cm) galvanized welded steel tubing
- Corrosion preventing interior/exterior galvanized steel coating
- Heavy-duty construction
- Swing away mast support
- TRM-3PN and TRM-5N accept up to 1¾ (4.4 cm) mast
- TRM-10L accepts up to 2¼ (5.7cm) mast
- TRM-3PN boxed for easy storage
- TRM-3 & 5 wind load test results available

SPECIFICATIONS

MODEL	SHIPPING DIMS in (mm)	WEIGHT lbs (kg)	COLLAR HEIGHT feet (mm)	LEG DISTANCE in (mm)	MAST OD in (mm)
TRM-3PN	60 x 7 x 6 (915 x 178 x 153)	8 (3.6)	3 (915)	32 (813)	1¾ (44)
TRM-5N	60 x 7 x 6 (1524 x 178 x 153)	13 (5.9)	5 (1524)	44 (1118)	1¾ (44)
TRM-10L	120 x 12 x 11 (3048 x 178 x 153)	50 (22.7)	10 (3048)	78 (1918)	2¼ (57)
TR2-5 BIPOD	60 x 7 x 6 (1524 x 178 x 153)	7 (3.2)	N/A	N/A	1¼/18ga/60 incl.

Wade Antenna's ongoing policy of continuing development may result in specification changes to its products.