

SD314-HF2P4SNM(D00-NUF) 4 dipole, 8 dBd, offset, N-Male, HD, Null Fill, 406-512 MHz

- Covers 406-512 MHz
- 8 dBd gain with offset pattern.
- 200W power handling
- Can be top or side mounted (Universal mount)

**Recommend SMK-125-A3 side mount kit when side mounting antenna.
Available from Sinclair separately.**

The SD314-H series is an extremely rugged 4-bay exposed dipole antenna designed for applications where the moderate gain is required. These premium-quality antennas are well suited to public safety applications.

The design of these antennas provides for coverage between 370 to 512 MHz in 2 subbands, 370-460 MHz and 406-512 MHz for private mobile networks, public safety, and public security networks.

Also available with an N-female connector as SD314-HF2P4SNF(D00-NUF).



www.sinctech.com

Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific
Telephone	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com

Electrical Specifications

Frequency Range	MHz	406 to 512	
Connector		N-Male	*1
Gain (nominal)	dBd (dBi)	8 (10.1)	*2
Input VSWR (max)		1.5:1	
Polarization		vertical	
Impedance	Ω	50	
Pattern		Offset	
Horizontal beamwidth (typ)	degrees	222	
Vertical beamwidth (typ)	degrees	16	
Average Input Power (max)	W	200	*3
Null fill	%	25	
Lightning protection		DC ground	
Electrical tilt (available)		0,2,4,6,8,or 10 degrees	

Notes

- *1 : N-Female available
- *2 : Gain variance ±1dB
- *3 : 300 Watts at 40 degrees C
- *4 : Qty 2
- *5 : Flat plate equivalent.

Mechanical Specifications


Width	in (mm)	12 (305)	
Depth	in (mm)	3.5 (89)	
Length/ Height	in (mm)	114 (2896)	
Base pipe diameter	in (mm)	2.38 (60)	
Base pipe mounting length	in (mm)	36 (914)	
Radiating element material		aluminum	
Base pipe material		aluminum	
Weight	lbs (kg)	23 (10.44)	
Mounting Hardware (Optional)		Clamp005, Clamp015, Clamp130, or Clamp125U	*4
Recommended For Offset Side Mount:		SMK-125-A3	
Mounting configurations		Universal Mount	
Actual shipping weight	lbs (kg)	35 (15.89)	
Shipping dimensions	in (mm)	118x4x20 (2997x102x508)	

Environmental Specifications

Temperature range	°F (°C)	-40 to +158 (-40 to +70)	
Wind Loading Area (Flat Plate Equivalent)	ft² (m²)	1.73 (0.16)	
Wind Loading Area (1/2" ice)	ft² (m²)	4.38 (0.41)	*5
Rated wind velocity (no ice)	mph (km/h)	215 (346)	
Rated wind velocity (1/2" radial ice)	mph (km/h)	155 (250)	
Lateral Thrust (100 mph No Ice)	lbs (N)	70 (311.4)	
Torsional moment (100 mph No Ice)	ft-lbs (Nm)	11 (14.9)	
Bending moment (100 mph No Ice)	ft-lbs (Nm)	132 (178.2)	

Ordering Information

Clamps must be ordered separately.



Region	United States	Europe, Middle East, and Africa	Canada, Caribbean, and Latin America	Asia-Pacific
Telephone	1 800 263 3275	+44 (0) 1487 84 28 19	Canada: 1 800 263 3275 International: +1 905 726 7676	+1 905 727 0165
E-mail	salesusa@sinctech.com	salesuk@sinctech.com	salescan@sinctech.com	salesasia@sinctech.com