

## SPECIFICATION CONTROL DRAWING


THIS DRAWING CONTAINS INFORMATION PROPRIETARY TO RF INDUSTRIES, LTD. ANY UNAUTHORIZED USE OF THIS DRAWING IS EXPRESSLY PROHIBITED. ANY VIOLATION IS PUNISHABLE UNDER U.S. COPYRIGHT LAWS.


REV	DESCRIPTION	DWN	DATE	APPROVED
Α	ENGINEERING RELEASE	CZS	9/2/99	R. RICE

ALL DIMENSIONS ARE REFERENCE ONLY









DIAMETER

DIMENSIONS ARE IN INCHES

UNLESS OTHERWISE NOTED

## SPECIFICATIONS:

IMPEDANCE: 50 OHMS

WORKING VOLTAGE: 1000 VRMS @ SEA LEVEL

FREQUENCY RANGE: 0-11 GHz

INTERFACE PER MIL-STD-348, SECTION 304.2

DRAWN
C. ZUNIGA 9/2
CHECKED

AND [MILLIMETERS]

TOLERANCES ARE:

DECIMALS

COMMECTORS

DIVISION OF RE INDUSTRIES, LTD.

7610 MIRAMAR RD SAN DIEGO,CA 92126 (858) 549-6340 (858) 549-6345 FAX

## RFN-1021-1

N FEMALE 4 HOLE FLANGE WITH REMOVABLE CAPTIVATED CONTACT

PRESS FIT FLANGE REMOVABLE CAPTIVATED CONTACT BRASS SILVER 9/2/99 DIELECTRIC **TEFLON** CABLE GROUP DWG NO. NONE SIZE REV 9/2/99 CONTACT PHOS BRONZE GOLD OR DRAWN 2 9241 BODY 1 BRASS SILVER 9/2/99 C. ZUNIGA CAD FILE 13ARC B TEM DESCRIPTION IOTY MATERIAL **FINISH** APPROVALS. DATE SCALE: 2:1 SHEET 1 OF